



Features

- 4K / 4 x 2 Megapixel Lens
- H.265 / H.264 compression
- 360 View and adjustable
- Built-in Micro SD Slot
- IK10 Protection

More Features

H.265+ / H.265 / H.264+ / H.264 / MJPEG coding

Max. Resolution: 4 x 2MP (1920 x 1080)

ICR auto switch, true day / night vision

3D DNR, WDR, HLC, BLC, smart IR, etc.

Built-in micro SD card slot, up to 256GB

IP 66/ IK10 ingress protection

Support dual streams

Support remote monitoring via smart phones & tablet PCs with iOS and Android OS

Intelligent analytics

ICR auto switch, true day / night vision

Specification	MIB-8160
Image Sensor	1 / 2.8 Progressive scan CMOSx 4ch
Image Size	Max Resolution (3840x2160)
Angle Adjust	Circular Slide 0-95, Vertically 40-70 4ch
Image Enhancement	DWDR, 3D DNR, Digital Zoom
Lens	4.00mm Lens x 4ch F1.6
Focus	Manually adjustable
Lens Mount	F1.6
Day & Night	IR Cut Filter
WDR	Digital WDR (Wide Dynamic Range)
Shutter Speed	1/1s – 1/100,000s
White Balance	Auto / Manually / Indoor/Outdoor
Gain	Auto / Manually
IR Distance	25m / 82.02ft - Meter radius
Video Compression	Main Stream H.265+, H.265, H.264+, H.264 Sub Stream H.265+, H.265, H.264+, H.264, MJPEG
H.265 Compression Standard	Main Profile @ Level 4.1 High Tier
Certification	IK10, IP66, ROHS, CE FC
Main Stream	Streams 1 to 4 / 60Hz: 1080P/ 720P 1-30fps/50Hz 1080P/ 720P 1-25fps
Sun Stream	Streams 1 to 4 / 60Hz: D1/CIF 1-30fps / 50Hz D1/CIF 1-25fps
Bit Rate	128Kbps- 4 Mbps
Bit Rate Type	VBR/ CBR
Image Setting	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image, Mirror, Image Flip, NR, etc., adjustable through client software or Web browser
Network	RJ45
Audio	G.711 A/U
Storage	Built-in Miro SD slot Up to 256GB
OnVif	Support
Power Supply	AC24/ DC 24V / PoE+
Power Consumption	< 25 W with IR ON
Operating Temp	- 30 °C ~ 60 (-22 °C °F~140°F);Humidity: less than 95 %
Dimension	273mm x 180mm / 10.7in x 7in
Certificate	CE, FCC
Weigh	Approx 3.26KG / 7. Lbs