



ToughEye™ 1700 OPT-1700K Self-Cleaning IP Camera



Features

- Triple Stream H.265 & H.264 & M-JPEG
- 2 Megapixel (1920x1080) @ 30fps
- Self Cleaning lens
- RJ45 Connection (M12 Optional)
- IP-67 Weatherproof / Dustproof

Product Options

OPT-1700K-80-M12

M12 Connection
IP PoE via M12 Connector
80° FoV Lens

OPT-1700K-100-M12

M12 Connection
IP PoE via M12 Connector
100° FoV Lens

OPT-1700-IVL

Integrated Visible Light
1500 lumens (output at 20c)
3800 lux at 30cm (output 20c)
4000K Color Temp

OPT-1700-128S

128GB Internal Storage

Specification	OPT-1700K-80	OPT-1700K-100
Imaging Sensor	2 Megapixel	
Lens	80° FoV	100° FoV
Resolution	Full HD (1920 x 1080) @ 30fps	
Min. Illumination	Color : 0.001 lux / B/W : 0.0001 lux (F1.2, AGC ON)	
Wide Dynamic Range	True WDR (>120dB)	
Fov Option	80 (Hor 80 & Ver 50) & 100 (Hor100 & Ver 67)	
Video (IP)	h.265 / h.264 / MJPEG	
Video (Analog)	720 x 486 (NTSC) & 720 x 576 (PAL)	
Network	IPv4/v6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPOE, SMTP, DNS, UPNP, FTP, ARP, SNMP	
ONVif	Profile S , Profile G	
Recording	Network recording, Continuous, motion Local On-board recording option available (128 GB storage capacity)	
Dimensions	102mm x 178mm (4in x 7in)	
Weight	3.Kg (6.5lb) - 4.3Kg (9.5lb) with Braket & Sunshield	
Clean Cycle	Configurable Timer Based, Electrical Trigger (up to 24V)	
Max Wattage	25W	
Input Voltage	PoE+ 42.5-57 VDC / DC18-32 VDC	
Temperature Rating	-40C to 60C (-40F to 140F)	
IP Rating	IP67/IP69	
Vibration	30G (at the Camera) JIS-D-1601-1995	
Certifications	FCC, ICES-003, CE, IP67/IP69, JIS-D-1601-1995	

