



SVN-2532P16C

32 Channel H.265 DVR



Features

H.265 & H.264 Video Compression
 16 Port PoE Built-in & Dual Nic
 Support Add Recorder Feature
 Supports P2P, built in DDNS, DHCP
 Super Live Plus Mobile App

More Features

Support 12MP/ 8.4MP /
 5MP / 4MP / 4MP Lite /
 3MP / 1080P / 960P /
 720P / Recording

Add Recorder Feature

Utilizes the H.265 High
 Profile Compression
 format to ensure high-
 quality video at lower
 bitrate

NAT and QR Code
 functionality allows
 remote access with
 mobile devices and
 computers without the
 need for port-forwarding

Specification	SVN-2532P16C
Compression	Standard H.265 High Profile
CPU	Cortex A9
OS	Embedded Linux
Input	16 x PoE Built in
Resolution	12MP / 4K (8.4MP) / 5MP / 4MP, 3MP, 1080P, 720P,
IP Channels	32 Channel
Output	HDMI-1: 4K / 2K / 1920x1080 / 1280x1024, HDMI-2: 1920x1080 / 1280x1024 VGA x 1: 1920x1080 / 128x1024,
Audio port	32 Channel Via IP Camera Support
Two-way Audio	Take Up Channel One Audio Input
Record Resolution	12MP / 4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1
Record Bit Rate	32Kbps~256Mbps
Record Frame Rate	12MP @ 20 fps / 4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1 @ 30fps
Mode	Manual / Timer / Motion / Sensor / Analytic
IP Resolution	Up to 12MP Megapixel
Storage	4 x Hard Drive (Up to 12 TB each slot)
Play Back	Maximum 16 Channels
Search	Time Slice, Time, Event, Tag Search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Playback Function	Play / Pause / FF / FB / Digital zoom etc.
Playback Mode	Manual / Sensor / Motion / Exception
Network Port	16 port PoE, 2 LAN (Dual Nic)
Alarm Trigger	Record / Snap / Preset / E-mail etc.,
Network Interface	RJ45 10 / 100 / 1000 Mbps x 1
Network Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Interface Protocol	Multiple Online User Up to Ten
Smart Phone OS	iOS, Android
PTZ	IP Cameras Support
USB Port	USB 2.0 x 2: 1: Front Panel & 1 Rear Panel
Power Supply	ATX
Power Consumption	<30W (With out Hard Drive)
Operating Temperature	14°F~122°F (-10°C~50°C)
Dimensions	17.3in x 2.75in x 15.35in (440 mm x 70 mm x 390 mm) (W x H x D)