



SVN-2532P16C

32 Channel H.265 DVR



Features

- H.265 & H.264 Video Compression
- 16 Port PoE Built-in & Dual Nic
- Support Add Recorder Feature
- Supports P2P, built in DDNS, DHCP
- Super Live Plus Mobile App

More Features

Support 12MP/ 8.4MP / 5MP / 4MP / 4MP Lite / 3MP / 1080P / 960P / 720P / Recording

OnVif: Profile S & T

Add Recorder Feature

Utilizes the H.265 High Profile Compression format to ensure high quality video at lower bitrate

NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding

| Specification | SVN-2532P16C |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Compression | Standard H.265 High Profile |
| CPU | Cortex A9 |
| OS | Embedded Linux |
| Input | 16 x PoE Built in |
| Resolution | 12MP / 4K (8.4MP) / 5MP / 4MP, 3MP, 1080P, 720P, |
| IP Channels | 32 Channel |
| Output | HDMI-1: 4K / 2K / 1920x1080 / 1280x1024, HDMI-2: 1920x1080 / 1280x1024 VGA x 1: 1920x1080 / 128x1024, |
| Audio port | 32 Channel Via IP Camera Support |
| Two-way Audio | Take Up Channel One Audio Input |
| Record Resolution | 12MP / 4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1 |
| Record Bit Rate | 32Kbps~256Mbps |
| Record Frame Rate | 12MP @ 20 fps / 4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1 @ 30fps |
| Mode | Manual / Timer / Motion / Sensor / Analytic |
| IP Resolution | Up to 12MP Megapixel |
| Storage | 4 x Hard Drive (Up to 12 TB each slot) |
| Play Back | Maximum 16 Channels |
| Search | Time Slice, Time, Event, Tag Search |
| Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| Playback Function | Play / Pause / FF / FB / Digital zoom etc. |
| Playback Mode | Manual / Sensor / Motion / Exception |
| Network Port | 16 port PoE, 2 LAN (Dual Nic) |
| Alarm Trigger | Record / Snap / Preset / E-mail etc., |
| Network Interface | RJ45 10 / 100 / 1000 Mbps x 1 |
| Network Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP |
| Interface Protocol | Multiple Online User Up to Ten |
| Smart Phone OS | iOS, Android |
| PTZ | IP Cameras Support |
| USB Port | USB 2.0 x 2: 1: Front Panel & 1 Rear Panel |
| Power Supply | ATX |
| Power Consumption | <30W (With out Hard Drive) |
| Operating Temperature | 14°F~122°F (-10°C~50°C) |
| Dimensions | 17.3in x 2.75in x 15.35in (440 mm x 70 mm x 390 mm) (W x H x D) |
| OnVif | Profile S & T |